Sierra Turbines Drives Innovation for Microturbines

Manufacturing gas microturbines to be 40X more efficient, 10X more power density, and 50% lighter in weight



Roger Smith is breaking the rules of manufacturing. The chief executive officer of San Jose, California-based **Sierra Turbines Inc.**, he's discarded the industry's long-held belief that additive manufacturing (AM) is limited to prototyping and low-volume work. In fact, Smith plans to additively manufacture 95% or more of his microturbine components even when he reaches large-scale production.

Smith doesn't care that he's discarding several other industry beliefs, among them the notion that overhauling microturbines every 40 to 50 hours is acceptable. Smith is unhappy with much of the small-engine status quo. A microturbine has historically been a simplified version of its full-size counterpart; cost restrictions have always prohibited manufacturing complex features that would give microturbines improved performance. With a little radical thinking and a hefty dose of advanced technology, he's prepared to change it.



One of the key pillars of this advanced technology in Smith's arsenal is the metal AM system from manufacturer VELO^{3D}, located just a few minutes south of Sierra Turbines in Campbell. Says Smith, "We opened the company in 2017, and within the first year or so had pretty much scoured the planet for a 3D-printing process to produce our parts. That's when we learned about VELO^{3D}. We were all quite surprised—and pleased—to discover they are just down the street from us. It makes our work together that much easier."

The "we" in this story is Smith's team of scientific and technical professionals. Some have gas turbine expertise; others are extremely knowledgeable in software and control systems (Smith himself spent 19 years with Apple before launching Sierra Turbines). All have worked in Fortune 100 product environments. Together they boast a combined 70 years of industry experience, with each team member sharing the same goal—to design and manufacture better solutions for the burgeoning microturbine market.

Microturbines are suitable for a variety of applications, Smith explains. First and foremost of these is unmanned aerial vehicles, or UAVs. Where gas turbine engines weighing many thousands of pounds push commercial and military aircraft through the skies every day, microturbines perform a less dynamic, though just as important, task: powering the electric motors that keep UAVs aloft. "For future gas turbine development, we aim to leverage the power of additive manufacturing to integrate features such as an efficiency-boosting recuperator, printed-in sensors, and more novel insulating and cooling geometries."

They can also be used to charge the batteries that drive those motors, as range extenders, or in hybrid UAVs that alternate between batteries and motors. These same functions apply to land-based power generation needs, where microturbine-based systems not much larger than a washing machine serve as auxiliary power units (APUs) in backup generators and other standby electrical-generation needs.

Cross-section of a Sierra Turbines engine combustor highlighting the complexity of the interior. Notice the thin air foils and smooth lattice that helps the combustor effectively atomize fuel prior to combustion. With traditional manufacturing, this specific part would have required the assembly of 61 discrete components, but 3D printing consolidated it into a unified geometry with fine details and features that are unattainable via any other method.



The Aurelius Mk1 Project

Sierra Turbines named their microturbine "Aurelius Mk1," drawing on that historical period when engines were named after Greek or Roman mythology. Inspired by the Rolls Royce Olympus engines that first powered the Concorde supersonic airliner, Aurelius also happens to be the name of Smith's late father. Sierra Turbines intends to honor that namesake by challenging the status quo. The time between overhaul (TBO) for most small turbine engines averages 40 to 50 hours. Smith intends to raise that value to 1000+ hours, on par with commercial aircraft. He also plans to reduce engine weight to a kilogram or less, cut noise, and improve fuel efficiency, all while making the turbines easier to manufacture. These are lofty goals, yet ones shared by practically everyone making microturbines. He's confident that his team will succeed where others have failed, however, through a host of design improvements only made possible with advanced metal AM.



Benchmarking Sierra Turbines to Market Incumbents Engine design and performance metrics

	Sierra Turbines's Engine	Market Incumbent' Engine
Time Between Overhaul (TBO)	1000 hours	40-50 hours
Part Count	Consolidated unicore	60+ discrete parts
Weight	50% weight reduction	varies
Power Density	2000 watt hrs. per kg	200 watt hrs. per kg (lithium ion)

Smith sees his efforts as part of a bigger picture, work that will contribute towards a revitalization of the country's manufacturing sector. "My thoughts are these," he says. "If we as a country are to start building products in the U.S. again, we must develop better ways of designing and fabricating products. This includes less reliance on tooling, most of which has been shifted to China, but also an embrace of Industry 4.0 and other change-making technologies. Metal 3D printing is one of these change-makers. It's far less wasteful than traditional manufacturing and presents endless opportunities for part consolidation, lightweighting, greater product efficiency...the list goes on."

One example of this new approach to design efficiency is the Aurelius combustor. It's the heart of any microturbine and the test case by which Smith would determine which providers were able to deliver on the promise of additive. The component contains hundreds of small, oddly shaped holes, delicate mesh-like webbing, dozens of internal cooling channels, and a series of thin, exceedingly tall walls. And where the initial design contained 61 discrete parts, that number fell to a consolidated "unicore" engine after Sierra Turbine's designers gave it an additive makeover with computational modeling software tools.

Key Differentiators

It's this highly sophisticated design that Smith presented to various additive equipment manufacturers, challenging them to build the part from Hastelloy® X, a high-strength, low-creep metal that's favored by commercial-aircraft manufacturers. The heat-resistant superalloy is also vital to Smith's reliability and fuel-efficiency goals, as it will allow his engine to reach temperatures previously unattainable in microturbines. "The hotter you go in any gas turbine, the better the performance," he says.



Cross-sections of the 3D printed engine core. 3a illustrates the necessary support structures if printed on incumbent AM systems, making this a poor business case for AM. 3b illustrates the value of VELO3D's support-less printing process, with the blue portion highlighting a smoothly blended lattice geometry, designed with nTopology's optimization software, which has the unique ability to spatially vary lattice size and thickness to maximize engine output and performance. 3c is the final printed part off the Sapphire printer, after it was removed from the build plate.

"Metal 3D printing is one of these change-makers. It's far less wasteful than traditional manufacturing and presents endless opportunities for part consolidation, lightweighting, greater product efficiency... the list goes on." Smith isn't naming names, except to say that "everyone else failed" in their attempts to build the thin-walled, high-aspect-ratio combustor. "The team at VELO^{3D} worked with us on the design, tweaking things to make it more manufacturable, but it was their Flow software that was perhaps the biggest enabler," Smith says, "It contains a number of special tools that provide valuable feedback throughout the entire print-preparation process."

He noticed a range of hardware differentiators as well. "It was obvious to me early-on that the VELO^{3D} platform offers a different approach to laser powderbed fusion (LPBF)," he adds. "For starters, their noncontact recoater blade is especially well-suited to print thin-walled sections—in some areas, our walls are less than one millimeter thick, and these tended to break off on other 3D printers." Smith also notes VELO^{3D}'s ability to eliminate supports on shallow overhangs. This attribute provides for internal features that would otherwise be impossible to produce, as well as the smooth surface finishes printed by the Sapphire metal AM system. Each of these reduces the need for secondary machining and other finishing processes, something the team at Sierra Turbines wishes to avoid wherever possible

Finally, the system's quality assurance software, Assure, documents all the critical sensor data that affect part quality and produces a comprehensive build report for traceability. Armed with data points concerning protrusions, oxygen level, filter life, and laser alignment, Sierra Turbines has confidence that the part built was indeed a good part. "This level of quality assurance is what will move the AM industry forward," notes Smith.



Taken directly out of the Assure build report and showing actual data from the Sierra Turbines project, see data related to Peak Height and Filter Recirculation. Peak Height measures concerns against protrusions, and the Recirculation Filter measures the life of the filter during the build. Both show no concern as the sensor readings are under the warning threshold.

Reducing the Pain of Traditional Manufacturing

The cost and energy savings by the consolidation of 61 parts into one part cannot be overstated. Production and transport of different raw materials, manufacture of individual parts using different processes, shipping of individual parts, tedious assembly work, joints of dissimilar materials, reliance on extra seals or fasteners, and more: All of this waste is simply eliminated by the integration of many parts into one printed part which subsequently requires minimal post-processing. "3D printing eliminates a great deal of manufacturing pain," Smith says.



Machine health snapshot from the Assure build report, showing that all critical sensors are calibrated. Laser alignment, laser focus, and beam stability have always been major concerns for the AM industry as it's common for alignment to drift during builds. Assure captures this data to communicate confidence to the customer.

Beam Stability	Value S	tatus Timestamp		р	Laser Alignment			Value	Status	Timestamp
Optics Box + Window					Overlay Variation - x direction			23		2020/07/02 at 08:45
Laser 1	34.328	\bigcirc	2020/07/02 at 14:29		Overlay Variation - y direction			34		2020/07/02 at 08:45
Laser 2	16.813	9	2020/07/02 at 14:29		Laser Overlav - x direction			0		2020/07/02 at 08:45
Optics Box						a orenay	Adirection	•	•	2020/07/02/00/00
Laser]	-30.014		2020/07/02 at 14:29		Laser Overlay - y direction			-14	\sim	2020/07/02 at 08:45
lasor 2	17702		2020/07/02 at 14:29		Laser Mapping Accuracy - x direction			73	\bigcirc	2020/07/02 at 08:45
000012 177702			2020/07/02/01/4/25		Laser Mapping Accuracy - y direction			78	Ø	2020/07/02 at 08:45
Thermal Sensor Alignment Value		Status	Timestamp		Lase	ser Focus Value		Status	s Timestamp	
Offset - x direction					Spot Si	ze Center F	ocus			
Laser 1	0.022	9	2020/07/02 at 14:29		Laser 1 -1.635		-1.635	\bigcirc	2020/07/02 at 14:43	
Laser 2	0.068	0	2020/07/02 at 14:29		la	Laser 2 -3.849		Ø	2020/07/02 at 15:08	
Offset - y direction					Spot Size Focus Across Build Plate					
Laser 1	0.025	0	2020/07/02	at 14:29	Laser 1		15.236	Ø	1	2020/07/02 at 14:43
Laser 2	-0.08	\bigcirc	2020/07/02 at 14:29		Laser 2		10.662	\bigcirc	1	2020/07/02 at 15:08
		Powde	r Bed Stability	Value	Status	Timestamp				
					-	2020/07/02 14.42				

Ready for Takeoff

Smith is just getting started. Once the combustor has been thoroughly tested and benchmarked, he intends to pursue additional performance improvements. He's also planning to work on the microturbine's rotating components, an unorthodox move that many aerospace pundits would agree is beyond the pale. Here again, Smith is determined. "VELO^{3D} believes that you can use additive for full-scale production, and so do I," he says. "For future gas turbine development, we aim to leverage the power of additive manufacturing to integrate features such as an efficiency-boosting recuperator, printed-in sensors, and more novel insulating and cooling geometries."

Nor is his decision solely a matter of lower cost, shorter lead-times, or abbreviated supply chains. By allowing Sierra Turbines to consolidate dozens upon dozens of components into a single 3D-printed piece, one with lower mass and greater mechanical integrity than the welded and assembled alternative, support-free printing technology is enabling this small company to meet its design goals. Smith fully expects to meet or exceed his TBO goal of 1000 hours, among other objectives.

"My design team is freed from the constraints of traditional manufacturing and even existing metal AM technologies such that they can focus purely on defining the geometry needed to maximize performance and differentiation."

Roger Smith

Founder and CEO, Sierra Turbines



Headquarters 511 Division Street Campbell CA 95008

www.velo3d.com info@velo3d.com

SierraCaseStudy.EN.20200810.V1-1.U.USL 0905-XXXXXA ©2020 VELO3D, Inc. All rights reserved. VELO and VELO^{3D} are registered US trademarks of VELO^{3D}, Inc